
GDI Communications LLC

Transportation Communications Specialists

Model SM336 Series 33.6K Dialup Modem



Features

- * Standard "AT" Command Set
- Dual RS232/RS485 Interface
- * Call Monitor Speaker
- * Error Correction / Data Compression
- * Integral Power Supply
- * Rugged Metal Enclosure
- * Wide Operating Temperature Range -37 to +74°C
- * Standalone or 170 Plug-in Card

Description

The GDI Smart Modem SM336 is an AT command set compatible dial-up modem. This modem has been designed specifically for the demands of the traffic industry. The GDI Smart Modem SM336 can be used to communicate with traffic controllers, variable message signs, dial-up to the web or most any other dial-up application that requires communications over the public switched network. The GDI Smart Modem SM336 offers 26 data rates from 300 to 33,600 bps. The GDI Smart Modem SM336 is "AT" command set compatible with auto-dial, auto-answer, and auto-speed detect. The GDI Smart Modem is compatible with the GDI Smart Modem SM336 dial-up modem. The internal fused power supply eliminates the common "brick" external power supply. The unit is also available in a 170 Plug-in form factor.



ENGINEER'S REVIEW

FENCINEER'S REVIEW

RESPONSE REGIRED

OF CONTRACTOR

Approved [] Comments Attached [] Confirm

Approved As Noted [] Received

If the Approved As Noted [] Received to Received as Approved

The Engineer's review of the other converties freeded to the consecution of the review of the other converties the Conference and restricted and research the other plants appetituations, and for the orthogonal train review to be received to the Conference area of the other and discussions of Indianation and Indianations and Indianations and Indianations and Indianation and Indianations and Indianation and Indianation and Indianations and Ind

Warlin Controls Inc.

980 Quaker Highway • Uxbridge, MA 01569 Tel: (508) 278-0446 • Fax (508) 278-0447