

PVH-157

Arnold St.

Chancery St. to Park St.

PART	KIND AND THICKNESS					JOINTS	AREA	COST PER SQ. YD.	LAID BY	YEAR	NOTE BOOK	REMARKS
	TOP	CUSHION		BASE								
24' WIDE												
N+s. of track	W.B. macadam											
In track	Stone block											
Full width	Bit. Conc. 1 1/2"	Bit. Conc. 1"		1-3-5 Concrete 5"					City	1916	418A-64	
Full width.	Warcolite 2"			Cr. Stone 3"		Dust			Middlesex			Warcolite by
									Const. Co	1939		Warren Bros
												P.W.A.

Library Bureau K65766

Asphaltic Concrete Laid Oct 1916

Top course

Bitumen	10.25%	70 lbs
Sand & dust	88.75	590 "
Stone	1.0	

Sand grading

Passing 200	156%
100	157
80	95
50	30.1
40	11.8
30	9.1
20	4.6
10	3.6

Binder Course

Bitumen	48%	30 lbs
Sand	16.1	
Stone	79.1	600 lbs.

Stone grading

Passing 200	24 1/8
100	22
80	16
50	28
40	16
30	12
20	12
10	4.2
X	2.9
1/4	29.5
1/2	49.4
3/4	1.1