

to Jenny Lind St

PH 1582

PART	KIND AND THICKNESS				JOINTS	AREA	COST PER SQ. YD.	LAID BY	YEAR	NOTE BOOK	REMARKS
	TOP		CUSHION	BASE							
60' WIDE No of track	Water bound	macadam						City			
No of track	Bit. conc.	2'-3"		c. stone				City	1915	H&H	over Thickness varies
sof track	Warrenite	2"		Cr. Stone 6"				Warren Bros.	1924		base by city
In track	Warrenite	2"		Grouted. St. Block				Warren Bros.	1926.		
Full width.	Bit. Conc.	2 $\frac{1}{2}$ "	Track space 24' wide Cr. Stone 3"	1 $\frac{1}{2}$ gals. Asp. Pen }	outside of track space Bit. Conc. laid over old pavement			D. P. W.	1946		Rails removed

Asphaltic Concrete Mixture laid Nov. 19, 1915.

Bitumen	10.1 %	80 lbs.
Sand	59.5 %	470 "
1/2 in, stone	25.2 %	200 "
Cement	5.2 %	40 "

Sand grading

Retained on No.10	6.5 %
Passing " 10	3.5 %
20	3.1 %
30	6.1 %
40	11.3 %
50	34.2 %
80	10.1 %
100	18.4 %
200	6.8 %

100.