

226 Ash St. ✓

Oct. 25, 1963

#26506 Bristol County House of Correction
E.S. 226 Ash St., S x Union St.
N

Please install 6" Fire Supply to
supply prison.

Measures of 6" O-ring Darling Tapping Gate:

W x E line Cedar Street 21.2 ft.

N x S " Court Street 12.6 ft.

Work done November 5, 8, 8, 12, 13, 14, 15, 1963

Measures of 6" O-ring Darling Hydrant Gate:

E x Center of hydrant 6.6

S x S line of Inside-Gate-Wall 15.7

Installed an 8"x6" tapping sleeve in the Court
St. main; and, then installed 6" Cast iron pipe
from there to the courtyard inside the House of
Correction with hydrant, hyd. gate & tee at end

97.4' of 6" C. I. Cement Lined Pipe...	
Labor.....	455.51
1 6" on 8" Tapping Sleeve - P. Smith.	
1 6" O-ring Darling tapping gate valve	
1 6" O-ring Darling All Bell gate val.	
2 6" C. I. gate boxes, compl- 44.80 ea.	89.60
1 6"x6"x6" tee, All Bell, Cen. Lined..	
1 6" Cast iron plug.....	
1 4" B-50-B Darl. hyd. 6" B.L.V. 13.2H	
74 lbs. leadite.....	
5 lbs. braided jute.....	
1 street cut: 6' x 3' Warrenite.....	
1 sidewalk cut: 8' x 4' cement.....	
Drilling Machine use.....	20.--
Compressor use.....	120.--
Loader use.....	120.--
Supervision.....	140.--

For removal and capping of old hydrant
inside courtyard of House of Correction,
November 21, 1963:

Labor.....	\$ 55.68
Carting.....	5.--
Compressor use.....	7.50
1 5/7" x 12" sq. steel plate with bolts and gasket.....	\$ 10.--
Supervision.....	6.67
	\$ 84.85

